

# G-TAS

# 柴油引擎發電機組 GENERATING SET

DOOSAN SERIES			RATINGS (kw) / 額定輸出 (仟瓦)				APPROXIMATE DIMENSIONS 開放型約略尺寸			
S/no	genset model	engine model	50hz/1500rpm		60hz/1800rpm		L/長	W/寬	H/高	weight/重量
序號	發電機組型號	引擎型號	prime	standby	prime	standby	mm	mm	mm	kg
1	GDD-20	DC23	14	16	18	20	1700	770	1250	650
2	GDD-26	DB33	20	22	24	26	1700	780	1350	780
3	GDD-50	P034TI	36	40	45	50	1800	780	1350	850
4	GDD-60	DB58	42	48	55	60	1900	800	1450	900
5	GDD-80	D1146	58	64	72	80	2240	800	1550	1300
6	GDD-100	D1146T	72	80	90	100	2240	800	1550	1500
7	GDD-125	D1146T	90	100	104	125	2350	800	1550	1550
8	GDD-150	P086TI-1	108	120	135	150	2750	960	1500	2100
9	GDD-175	P086TI-1	120	132	155	175	2750	960	1500	2100
10	GDD-200	P086TI	160	176	182	200	2750	990	1500	2300
11	GDD-250	P126TI	203	225	225	250	3000	1100	1420	2300
12	GDD-300	P126TI-2	-	258	-	300	3000	1100	1420	2300
13	GDD-350	P158LE-1	288	320	320	350	3000	1386	1773	2650
14	GDD-400	P158LE	320	352	364	400	3000	1386	1773	2700
15	GDD-450	DP158LC	355	390	400	450	3000	1386	1773	2700
16	GDD-500	DP158LD	400	440	445	500	3100	1387	1743	3600
17	GDD-600	DP180LB	480	528	541	600	3300	1380	1775	4100
18	GDD-750	DP222LC	594	660	675	750	3663	1620	1900	4600

prime power : Overload of 10% is permitted for one hour in twelve hours operation.

連續輸出：每12小時運轉中，具有超載 10% 1個小時的能力。

standby power : no overload is permitted.

緊急輸出：無超載能力之最大輸出容量。

