

G-TAS

柴油引擎發電機組 GENERATING SET

CUMMINS SERIES			RATINGS (kw)/額定輸出(仟瓦)		APPROXIMATE DIMENSIONS 開放型約略尺寸				
S/no 序號	genset model 發電機組型號	engine model 引擎型號	EPA Emissions Level	60hz/1800rpm		L/長 mm	W/寬 mm	H/高 mm	weight/重量 kg
				prime	standby				
1	GCD-150	QSB7G3	Tier3	163	186	2600	900	1550	2700
2	GCD-175	QSB7G4	Tier3	184	214	2600	900	1550	2700
3	GCD-200	QSB7G5	Tier3	208	242	3000	950	1600	2700
4	GCD-230	QSL9G2	Tier3	241	280	3000	950	1600	2700
5	GCD-250	QSL9G3	Tier3	262	297	3000	950	1600	2700
6	GCD-275	QSL9G4	Tier3	378	430	3100	1000	1650	2750
7	GCD-300	QSL9G5	UR	307	355	3100	1000	1650	3250
8	GCD-300	QSL9G7	Tier3	419	464	3100	1000	1650	3250
9	GCD-300	NTA855-G2	UR	313	347	3100	1000	1650	3250
10	GCD-350	NTA855-G3	UR	358	399	3400	1100	1650	3800
11	GCD-400	NTA855-G5	UR	-	451	3600	1300	1990	4300
12	GCD-400	QSX15G8	Tier2	444	500	3600	1300	1990	4300
13	GCD-450	KTA19-G3	UR	463	511	3600	1300	2020	4400
14	GCD-500	KTA19-G4	UR	507	563	3600	1300	2020	4500
15	GCD-500	QSX15G9	Tier2	507	563	3600	1300	2020	4500
16	GCD-600	VTA28-G5	UR	608	671	3900	1500	2100	6000
17	GCD-750	QSK23-G6	Tier2	768	854	4200	1660	2250	9000
18	GCD-800	QSK23-G7 NR2	Tier2	809	910	4200	1660	2250	9000
19	GCD-900	QST30-G3	UR	910	1007	4650	1900	2650	9400
20	GCD-1000	QST30-G4	UR	1007	1112	4200	1780	2270	9600
21	GCD-1000	QST30G5	Tier2	1007	1112	4200	1780	2270	9600
22	GCD-1250	KTA50-G3	UR	1300	1380	5200	1860	2450	10500
23	GCD-1250	QSK38G4	Tier2	1230	1376	5200	1860	2450	10500
24	GCD-1400	QSK50G3	Tier2	1395	1559	5200	1860	2450	11500
25	GCD-1500	QSK50G4	Tier2	1470	1656	5200	1860	2450	11500
26	GCD-1500	KTA50-G9	Tier1	1384	1656	5200	1860	2450	11500
27	GCD-1600	QSK50G6	Tier2	1574	1750	6000	2250	2720	16500
28	GCD-1750	QSK60-G10	Tier2	1830	2032	6000	2250	2720	16500
29	GCD-2000	QSK60-G6	Tier2	1975	2180	6000	2250	2720	18000

prime power:Overload of 10% is permitted for one hour in twelve hours operation.
standby power : no overload is permitted.

連續輸出：每12小時運轉中,具有超載 10% 1個小時的

緊急輸出：無超載能力之最大輸出容量。

