

G-TAS

柴油引擎發電機組 GENERATING SET

MTU SERIES			RATINGS (kw)/額定輸出(仟瓦)			APPROXIMATE DIMENSIONS 開放型約略尺寸			
S/no 序號	genset model 發電機組型號	engine model 引擎型號	EPA Emissions Level	60hz/1800rpm prime standby		L/長 mm	W/寬 mm	H/高 mm	weight/重量 kg
1	GMD-275	6R1600G70S	Tier3	-	312	3150	1200	1750	2800
2	GMD-300	6R1600G80S	Tier3	-	343	3150	1200	1750	2800
3	GMD-350	8V1600G70S	Tier3	-	408	2800	1320	1905	3200
4	GMD-400	8V1600G80S	Tier3	-	448	2800	1320	1905	3200
5	GMD-500	10V1600G80S	Tier2	-	561	3150	1320	1905	4150
6	GMD-550	12V1600G70S	Tier2	-	613	3300	1260	2030	4500
7	GMD-600	12V1600G80S	Tier2	-	668	3300	1260	2030	4500
8	GMD-700	12V2000G45	Tier2	710	780	3900	1700	2000	5500
9	GMD-750	12V2000G85	Tier2	810	890	3911	1580	2152	6000
10	GMD-800	12V2000G85	Tier2	810	890	4110	1580	2152	6000
11	GMD-900	16V2000G45	Tier2	915	1010	4430	1898	2300	6500
12	GMD-1000	16V2000G85	Tier2	1010	1115	4430	1898	2300	6700
13	GMD-1200	18V2000G85	Tier2	1191	1310	4600	2125	2500	8100
14	GMD-1600	12V4000G43	Tier2	1520	1736	5800	2085	2250	13000
15	GMD-1750	12V4000G83	Tier2	1736	1910	5800	2085	2250	13000
16	GMD-2000	16V4000G43	Tier2	2020	2280	6500	2200	2700	18000
17	GMD-2250	16V4000G83	Tier2	2280	2500	6500	2200	2700	18000
18	GMD-2500	20V4000G43	Tier2	2490	2740	8200	2400	3300	25000
19	GMD-2800	20V4000G83	Tier2	2740	3010	8200	2400	3300	25000
20	GMD-3200	20V4000G83L	Tier2	3010	3490	8200	2400	3300	25000

prime power : Overload of 10% is permitted for one hour in twelve hours operation.

連續輸出：每12小時運轉中，具有超載 10% 1個小時的能力。

standby power : no overload is permitted.

緊急輸出：無超載能力之最大輸出容量。

